

CL-S621 Bar Code/ Label Printer



The powerful CL-S621 offers unparalleled versatility in the desktop thermal printer class. Able to print in both direct thermal and thermal transfer mode the CL-S621 features a 360-meter ribbon for greater productivity and reduced down-time. Citizen's unique metal Hi-Lift[™] mechanism allows easy access for loading of media and/or ribbons and the adjustable media sensor can handle a wide variety of label configurations including standard and pediatric medical wristbands. The powerful on-board 32 Bit RISC processor delivers exceptional throughput and fast first label out. The CL-S621 comes standard with serial and USB interfaces. Optional parallel, Ethernet and Wifi interfaces are also available.

CITIZEN SYSTEMS AMERICA CORPORATION

CL-S621



CL-S621 Bar Code/Label Printer

Features

- n Powerful 32 Bit RISC processor
- n Thermal transfer or direct thermal printing
- n 360-meter ribbon
- n Standard and pediatric medical wristband capable
- n Metal Hi-Lift[™] print mechanism
- n Standard serial and USB interfaces
- Parallel, Ethernet and wireless LAN networking options
- n Internal 5-inch (125mm) media capacity
- Auto-Sensing Zebra[®] and Datamax[®] emulations
- n Ships with Windows[™] XP, Vista & Windows 7 drivers
- n Label design software included
- Active Ribbon Control and Positioning System (ARCP)
- n Internal power supply
- n Two Year Warranty

Applications

- n Healthcare
- n Pharmacy labeling
- n Postal service
- n Product labeling
- n Inventory control
- n Asset tracking



Torrance, CA 90501 • (310) 781-1460

Specifications

specifications		
Printing Method	Thermal transfer / Direct thermal	
Print Width	4.1" (max)	
Resolution	203 dpi	
Print Speed	4ips TT (6ips DT)	
Media Types	Roll or fanfold, Continuous or perforated, Die-cut labels, tags and tickets	
Paper Width (min/max)	.077" - 4.65"	
Paper Thickness	0.0025" - 0.01"	
Paper Roll Size	5" (max)	
Print Length (min/max)	.25" - 32"	
Ribbon Type	Wax, wax-resin or resin	
Ribbon Length	1182' / 360m	
Emulations	Standard: DPL™ and ZPL™ Auto-Sensing	
Barcode Types	Linear Bar Codes: Code 11, Interleaved 2 of 5, Code 39, EAN-8, EAN-13, UPC-E, Code 93, Code 128, Industrial 2 of 5, Standard 2 of 5, ANSI CODABAR, LOGMARS, MSI, Plessey, UPC/EAN Extensions, UPC-A, POSTNET	
	2-Dimensional: Code 49, PDF-417, CODABLOCK, UPS Maxi Co Micro PDF-417, Data Matrix, QR Code	ode,
Media Sensing	Sensors: Transmissive and reflective media sensors	
Fonts	Standard: 11 system bit-mapped fonts including OCR-A, OCR-B, CG Triumvirate, CG Triumvirate bold and a True Type™ Rasterizer	
Memory	DRAM: 8 MB Flash: 4 MB	
Interface	Standard: RS232C, USB Optional: Ethernet, Wi-Fi or Parallel	
Drivers	Windows Drivers: Windows / XP / Vista / 7	
Power	120V, 2.4A, 60Hz	
Weight:	10.7 lbs	
Dimensions (W x D x H)	9.1" x 11.4" x 10.2"	
Options	Cutter, label peeler	
Warranty	Two years	Rev. 12/10
Ahearn & AUTO-ID &	Soper Inc. Solutions 100 Woodbine Downs Blvd. Toronto, ON M9W 556 Tel: 800-263-4258/416-675-3999 Québec: 800-361-9584	

www.ahearn.com

Western Canada: 800-468-7025